




YFT12

FEATURES:

- > Imported Eco-Power:
KUBOTA D1105 engine, EU V/EPA4 compliant, stable performance.
- > Precise Hydraulics: Pilot system for light, flexible, high-efficiency operation.
- > Flexible Compact Design:
Zero tail swing, retractable tracks, ideal for narrow spaces.



Specification

Bucket Capacity (m ³)	0.025
Swing Speed (rpm)	0-12
Gradeability (°)	35
Max. Bucket Digging Force (kN)	9
Max. Arm Digging Force (kN)	5.5
Engine Model	D722-E4B
Power/revolution speed (kW/rpm)	10.2/2500
Operating weight (kg)	1200
System Pressure (MPa)	17

Machine size

Dimension Length*Width*Height (mm)	3032x760/980x2270
Cabin Height (mm)	2270
Track length (mm)	1345
Wheel(track) Distance (mm)	580/760
Minimum ground clearance (mm)	125
Tail Swing Radius (mm)	550

Working range

Max. Digging Height (mm)	3107
Max. Dumping Height (mm)	2172
Max. Digging Depth (mm)	1838
Max. Vertical Digging Depth (mm)	1709
Max. Digging Reach (mm)	3442
Min. Swing Radius (mm)	1398
Counterweight Height (mm)	395
Ground length(Transportation) (mm)	1597